Waterproof Sealant



KEY FEATURES:

- 100% Waterproof & Vapor Proof
- High Compressive Strength (>300 kPa)
- Thermal Insulation & Energy Saving
- Lightweight & Easy to Cut / Install
- Pre-coated Surface Ready for Direct Tiling
- Rot-proof & Mold Resistant

Item	Standard	Value
Chemical Base	/	MS Polymer (Modified Silane)
Curing System	/	Moisture Curing
Curing Rate (24h)	ISO 291 (23°C/50%RH)	380 g/m²
Skin Formation Time	ISO 291 (23°C/50%RH)	≥ 2.5 mm / 24h
Shore A Hardness	ISO 868	50 ± 5
Tensile Strength	ISO 37	≥ 2.2 N/mm²
Elongation at Break	ISO 37	≥ 350%
Elastic Recovery	ISO 7389	≥ 70%
Joint Movement Capability	ISO 11600	± 25%
Shear Bond Strength	EN 1465	≥ 1.5 N/mm²
Application Temperature	Manufacturer Spec	+5°C to +40°C

Certified Quality
Trusted Performance

CE · WATERMARK · SASO · GECA · CodeMark™ · B1 Fire Rating

https://www.heatfloorpro.com | info@heatfloorpro.com
WhatsApp | Phone number： +86 136 9125 9651
Making Construction Easier!